



Technical characteristics of PDU FRA16367

Model	19" PDU IN PLASTIC
Product code	FRA16367
Size	19" (horizontal positioning)
Structure	Plastic
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	Schuko-type 16 A
Output plug	6 Schuko/Italian 10/16 A-type
Length of power-supply cable	3 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	16A
Switch	Illuminated, red
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack



Technical characteristics of PDU FRA16342

Model	19" PDU IN METAL
Product code	FRA16342
Size	19" (horizontal positioning)
Structure	Metal
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	Schuko 16 A-type
Output sockets	8 Schuko/Italian 10/16 A-type
Length of power-supply cable	2 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	16A
Switch	Illuminated, red
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack



Technical characteristics of PDU FRA16343

Model	19" PDU IN METAL
Product code	FRA16343
Size	19" (horizontal positioning)
Structure	Metal
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	Schuko 16 A-type
Output sockets	6 Schuko/Italian 10/16 A-type
Length of power-supply cable	2 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	16A
Switch	Thermal-magnetic 16A
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack



Technical characteristics of PDU FRA16345

Model	19" PDU IN METAL
Product code	FRA16345
Size	19" (horizontal positioning)
Structure	Metal
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	IEC320 C20-type
Output sockets	8 Schuko/Italian 10/16 A-type
Length of power-supply cable	2 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	16A
Switch	Thermal fuse 16A with illuminated LED
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack

Technical characteristics of PDU FRA16353

Model	19" PDU IN METAL
Product code	FRA16353
Size	19" (horizontal positioning)
Structure	Metal
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	Schuko 16 A type
Output sockets	8 IEC320 C13-type
Length of power-supply cable	2 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	10A
Switch	Illuminated, red
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack



Technical characteristics of PDU FRA16354

Model	19" PDU IN METAL
Product code	FRA16354
Size	19" (horizontal positioning)
Structure	Metal
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	IEC320 C14 type
Output sockets	8 IEC320 C13-type
Length of power-supply cable	2 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	16A
Switch	Illuminated, red
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack



Technical characteristics of PDU FRA16355

Model	19" PDU IN METAL
Product code	FRA16355
Size	19" (horizontal positioning)
Structure	Metal
Dimensions WxHxD	48,3x4,4x6,8 cm (1 Rack unit)
Input plug	IEC320 C20-type
Output sockets	4 IEC320 C13 + 3 IEC320 C19-type
Length of power-supply cable	2 m
Power-supply cable section conductors	3x1,5 mm ²
Rated voltage	250 Vac
Rated current	16A
Switch	Thermal fuse 16A with illuminated LED
Safety protection	Childprotection
Certification	CE, Rohs Compliant
Colour	Black
Compatibility	19" Standard Rack

